# Architecture of Garnet Collaborative Portal

DoE Components Meeting
July 24 2001
Geoffrey Fox

IPCRES Laboratory for Community Grids
Computer Science, Informatics, Physics
Indiana University
Bloomington IN
gcf@indiana.edu

# Garnet Heritage/Assumptions

- Support Education, Training and if possible Computing as Grid(Web) Services
- Use best practice commercial and academic capabilities
  - Access Grid, HearMe, Anabas, (JMS, WSDL, EJB, Castor, Oracle etc.)
  - Worry about Centra, WebEx, Placeware, Blackboard, WebCT, Saba, Groove, Docent etc.
  - Respect IMS/ADL Learning Object standards (http://www.adlnet.org) and GGF Computing Objects
- Integrate Synchronous and Asynchronous ( "learning management system") collaboration
- Support hand held and desktop clients (universal access)

# **Garnet Technology**


- Uniform XML event (message) based architecture
  - Linked with a publish-subscribe paradigm
- XML Schema GXOS supports hierarchical data structures (compatible with DoD ADL SCORM for learning objects)
  - XML for all metadata (Users, documents, computers) and object changes -- from text chats to display changes etc.)
- Java Middleware using Enterprise Javabeans
- Production system uses JMS (Java Message Service) to implement publish-subscribe
  - JMS does Synchronous and Asynchronous Messaging
- MyXoS manages XML information nuggets

# **Important Capabilities in Initial Garnet**


- Standard stuff: built in shared display, whiteboard, HearMe Audio control, quizzes, annotations, chat/IM (Jabber.org)
  - Desktop video will be special case of shared display
- Record and replay all features of session (SMIL)
  - A/V, Presentation, Annotations, Text Chat
- Several Specialized Collaborative Shared Export Viewers: JSP, (later HTML, Acrobat ..)
- Initial SVG (Scalable Vector Graphics) Shared Batik Viewer
  - 2D Scientific Visualization/Whiteboard
  - Macromedia (Flash~SVG) and Adobe (already "all" to SVG)
- Initial source of SVG: Convert PowerPoint VML/WMF to SVG
  - Gives shared export model for PowerPoint with each client able to scale independently at high resolution

#### JMS (Java Message Service) Structure in Garnet

**Basic primitive is a topic/property labeled queue = JXTA Pipe** 



# Performance of Commercial JMS I




#### Peer to Peer P2P Networks


- Publish/Subscribe is mechanism we use to establish who gets what information for Collaboration and P2P and may be ALL Grid and ALL Web Services?
- Message (or event) services underlie P2P Grids
  - GMS can be built on top of JXTA or JMS architecture
- JXTA like MyXoS identifies the implicit distributed operating (control messages/metadata) system
  - Both have message queues as primitives
  - Both have Shell

9/5/2001

- Both use XML based messages
- JXTA Advertisements are similar to GXOS metadata for objects



#### Peers Peer to Peer Network



Peers are Jacks of all Trades linked to "all" peers in community


Typically Integrated Clients Servers and Resources








#### Peer to Peer Grid







#### P2P Grid Event Service – a better JMS

- Dynamic Collection of some billion computers each of which can either generate, route or consume events
- Publisher labels events by an (XML) object which is at simplest a URI but in general a collection of tag-values or instance of XML Schema
- Subscribers issue some sort of XML Query e.g. deliver all gxos://garnet/Education/Graduate/ComputerScience/ Indiana/Spring2001/CPS616/Lecture3/\*
- Need Secure, High Performance, Efficient (don't propagate events further than they need), Fault Tolerant delivery service
- Shrideep Pallickara PhD June 1 2001
- Current version Java RMI based could be SOAP

# Proposed GMS Model for Messages

All message publication labels and subscription profiles are defined in XML






We are moving from client – server – resource model with Clearly defined responsibilities to a Heterogeneous Dynamic Grid of service providers and Service consumers which are not necessarily distinct




#### Some Results – 22 Servers



#### Match Rates of 10% & Server Hop to client = 1


Subscriber 1 server hop from publisher - Matching 10%



#### **Event-based Garnet Architecture**

- All Objects are defined in XML (metadata)— this XML view could be "virtual" but can be used to discover, edit (etc.) objects — labeled by a URI
- GXOS manages meta data defining all Objects it doesn't really want to manage Objects, just information required to find, access, store, render and share it
  - MUST have a good object management system to build collaboration service
  - Rendering includes Palm devices as well as PC's
  - Entities are people, cuuricula, grades, computers etc.
- All actions including object changes are events all events are GXOS objects
  - Instant Messenger access, Framebuffer changes etc. are all GXOS events uniformly routed/archived etc.
- There is a Shell MyXoS with basic Services (copy, create, collaborate etc.) similar in concept to JXTA Shell

#### Overall Structure of GXOS for a MegaMeeting



#### Interface of XML and Java I

- How will we teach computing?
  - K-4: Internet Access
  - Middle School: (Simple) XML Schema interfaced to some scripting language
  - High School: Java as the programming model with Java classes (for external data) generated
- Probably don't want to specify objects twice
  - Start in Java; generate Schema
- Or Start with Schema and generate Java
- Need a natural API of computer code to real or virtual XML
  - Current mechanisms seem quaint (JDBC), inefficient (parsers), or non standard (Castor)

#### Interface of XML and Java II

Suppose we have a quadrillion (10<sup>15</sup>)
 XML objects as say produced by a
 physics accelerator per year
 (Enterprise GXOS)




(Virtual) XML View

Need to combine:

Search Interface to select nodes of XML
 Tree

- Specify URI
- JDBC or Google like Interfaces
- Castor like Interface to map XML into Java but need to control depth of conversion from XML into Java



#### **Current GXOS API Architecture**

- Initially implement "Personal GXOS" Information Repository small enough that we can afford to read all possibly relevant information into memory and refine this
  - E.g. Support course data for individual faculty
- File.xml → XML Object → Java Object and vice versa
  - Use Castor to automate XML Schema to Java Object
- Primitives Supported Initially
  - Get a "leaf Object"
  - Get a Collection (Internal Node) "handle" and self.xml (the GXOS properties associated with this node)
  - List Contents of a collection (recursively)
  - Get Contents of a collection (recursively)

# Integration of Hand Held Clients

- Client Device (machine) Profile stored in GXOS specifies O/S, default Screen Size modified by user (person) preferences
  - Dynamically updated with connection bandwidth, user updates
- Application Profile stored in GXOS and modified by event stream specifies data delivered by GMS
- Adaptor (Personal Server) looks like a conventional client to GMS and adapts data to specified client/user specifications
  - If PDA "small", then SVG viewer on "adaptor" and ship framebuffer to PDA
  - "Resize" on PDA handled by adaptor, scrolling by PDA etc.
  - Adaptor can process complex XML queries



Linking Desklop and Hand Hed Desices

Shared Display

